

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :	A1	(11) International Publication Number:	WO 96/23850
C09K 15/28, 15/32, B32B 15/04		(43) International Publication Date:	8 August 1996 (08.08.96)

(21) International Application Number: PCT/US95/09722

(22) International Filing Date: 3 August 1995 (03.08.95)

(30) Priority Data:
383,122 3 February 1995 (03.02.95) US

(71) Applicant: OLIN CORPORATION [US/US]; 350 Knotter Drive, P.O. Box 586, Cheshire, CT 06410-0586 (US).

(72) Inventors: KAPPOCK, Paul, S.; 129 A Clark Hill Road, East Hampton, CT 06424 (US). WALDRON, Craig; 101-19 Hitchcock Road, Waterbury, CT 06705 (US).

(74) Agents: CARLSON, Dale, Lynn et al.; Wiggin & Dana, One Century Tower, New Haven, CT 06508-1832 (US).

(81) Designated States: AM, AU, BB, BG, BR, BY, CA, CN, CZ, EE, FI, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LV, MD, MG, MN, MW, MX, NO, NZ, PL, RO, RU, SD, SG, SI, SK, TJ, TM, TT, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: DISCOLORATION PREVENTION IN PYRITHIONE-CONTAINING COATING COMPOSITIONS

(57) Abstract

Disclosed is a process for inhibiting the formation of discoloration in an aqueous composition selected from the group consisting of water-based paint, adhesive, caulk and sealant compositions, and combinations thereof, wherein said discoloration is caused by the presence of ferric ion or cupric ion together with pyrithione in said composition. The process comprises contacting the composition with a discoloration-inhibiting amount of a zinc compound selected from the group consisting of zinc salts of organic acids, zinc salts of inorganic acids, zinc hydroxide, zinc oxide, and combinations thereof. Also disclosed is an aqueous antimicrobial composition protected against discoloration attributable to the presence of ferric ion or cupric ion therein.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

DISCOLORATION PREVENTION IN
PYRITHIONE-CONTAINING COATING COMPOSITIONS

This invention relates generally to coating compositions, and, more specifically, to methodology for preventing or reducing discoloration in pyrithione-containing coating compositions.

5 Sodium pyrithione (also called the sodium salt of 1-hydroxy-2-pyridinethione, sodium pyridine-2-thiol-N-oxide, or 2-pyridinethiol-1-oxide, Na salt) has excellent antimicrobial properties, and is typically employed as a biocide and preservative in
10 functional fluids, such as metalworking fluids, lubricants, cosmetics and toiletries. Sodium pyrithione is a well-known commercial product commonly made by reacting 2-chloropyridine-N-oxide with NaSH and NaOH, as disclosed, for example, in
15 U.S. Patent No. 3,159,640.

Likewise, zinc pyrithione [also known as zinc pyridine-2-thiol-N-oxide or bis [1-hydroxy-2(H) pyridinethionato]-zinc] is an excellent antimicrobial additive. Zinc pyrithione may be made
20 by reacting 1-hydroxy-2-pyridinethione or a soluble salt thereof with a zinc salt (e.g., ZnSO₄) to form a zinc pyrithione precipitate, as disclosed, for example in U.S. Patent No. 2,809,971. Zinc pyrithione has been employed as a broad-spectrum
25 anti-microbial agent and preservative in metalworking fluids, plastics, paints, adhesives and cosmetics. Its principal uses are as an anti-dandruff agent in hair products, as a preservative in various cosmetics, and as an antifoulant in
30 marine paints. The commercial use of zinc pyrithione in paints, adhesives, caulk and sealants is growing.

In the presence of ferric ion, sodium or zinc pyrithione-containing compositions tend to turn blue even though the ferric ion is present in mere trace amounts. This blue discoloration is undesirable for 5 aesthetic reasons, as well as for functional reasons relating to unwanted color formulation.

More specifically, since the aesthetics of paints, adhesives, caulk and sealants normally require certain desirable colors, and since the 10 formulators of such products go to great lengths to achieve specific color effects, any ingredient which causes the formulation to vary much from a desired white or colorless (i.e., "water white") hue may make the colorant formulators' task very difficult. 15 More specifically, when attempting to utilize pyrithione as an antimicrobial agent in fully-formulated water-based paints, paint bases (i.e., the partially formulated paint before pigment addition), adhesives, caulk and sealants, an 20 unwanted color in an additive can adversely affect the color of the formulated product. Thus, the discoloration typically adversely affects the desired color, producing an off-color product.

In addition to the aesthetics problems and 25 colorant functioning problems, the blue coloration problem associated with the presence of ferric ion causes a performance problem in the sodium pyrithione-containing compositions. This performance problem when using sodium pyrithione 30 results from the fact that the pyrithione tends to form a blue precipitate in the presence of ferric ion. The precipitate reduces the amount of

-3-

available pyrithione throughout the composition, thereby diminishing the biocidal protection thereof.

In the past, various solutions to the blue discoloration problem have been proposed. By way of 5 illustration, U.S. Patents 4,957,658 and 4,818,436 disclose solutions to the above-discussed discoloration problem attributable to the presence of ferric ion plus pyrithione, in paints and functional fluids (e.g., metalworking fluids) 10 respectively, by adding to the paint or functional fluid an alkali metal or alkaline earth metal salt of 1-hydroxyethane-1,1-diphosphonic acid. Although the '658 and '436 patents propose good solutions to the discoloration, these solutions are not always as 15 cost effective or permanent as might be desired.

As another illustration, U.S. Patent 4,161,526 discloses a white to cream yellow pyrithione, pyrithione salt or dipyrithione for application to skin or hair containing from about 0.01 percent to 20 about 1 percent of the zinc salt of an organic carboxylic or inorganic acid, zinc hydroxide or zinc oxide, or a mixture thereof. The composition of the '526 patent is said to be effective in preventing or removing discoloration caused by formation of a 25 colored pyrithione, pyrithione salt, or dipyrithione contaminant (said to be iron pyrithione) in the composition. Unfortunately, the '526 patent does not teach a solution to the discoloration problem in compositions unrelated to skin or hair care, and not 30 containing iron pyrithione. Furthermore, the '526 patent teaches the use of higher levels of the zinc salt, zinc oxide or zinc hydroxide than otherwise might be desired.

New solutions to the blue and green discoloration problem in various aqueous compositions, particularly paints, adhesives, caulks and sealants which enables pyrithione to be utilized 5 therein in the presence of iron or copper, without any resulting discoloration of the composition, and that is cheaper, longer lasting, and/or uses lower levels of additives than required by the above-discussed prior art, would be highly desired by the 10 paint, adhesives, caulks and sealants manufacturing community. The present invention provides one such solution.

In one aspect, the present invention relates to a process for inhibiting the formation of 15 discoloration (e.g., a blue, grey, or green off-color formation) in an aqueous composition selected from the group consisting of water-based paint, adhesive, caulk and sealant compositions, and combinations thereof, wherein said discoloration is caused by the presence of ferric ion or cupric ion 20 together with pyrithione in said composition, which comprises contacting the composition with a discoloration-inhibiting amount (advantageously between 10 ppm and 90 ppm, more advantageously 25 between 10 ppm and 70 ppm, based upon the weight of the composition) of a zinc compound selected from the group consisting of zinc salts of organic acids (e.g., zinc acetate), zinc salts of inorganic acids (e.g., zinc sulfate and zinc chloride), zinc 30 hydroxide, zinc oxide, and combinations thereof.

In another aspect, the present invention relates to a process for removing an undesirable discoloration in an aqueous antimicrobial

composition containing a dissolved metal ion selected from the group consisting of ferric ion, cupric ion, and combinations thereof, and containing pyrithione (preferably in an antimicrobially effective amount), which comprises contacting said composition with a zinc ion in a molar amount at least equal to the amount of said dissolved metal ion in said composition. Advantageously, the zinc ion is present in the composition in an amount of 5 between 10 ppm and 90 ppm, more advantageously between 10 ppm and 70 ppm, based upon the weight of 10 the composition.

In yet another aspect, the present invention relates to an aqueous antimicrobial composition, 15 protected against discoloration attributable to the presence of ferric ion or cupric ion therein, said composition being selected from the group consisting of water-based paints, adhesives, caulk and sealants, and combinations thereof, said composition comprising water, an organic base medium and zinc ion, said zinc ion being present in said composition 20 in an amount of between 10 ppm and 90 ppm, more advantageously between 10 ppm and 70 ppm. The zinc ion is suitably provided in said composition by the incorporation therein of a zinc salt of an organic acid or inorganic acid, zinc hydroxide, zinc oxide, 25 or a combination thereof in order to provide the desired amount of zinc ion.

In still another aspect, the present invention 30 relates to a coated substrate comprising a substrate selected from the group consisting of ferrous metal-containing substrates, copper-containing substrates, and combinations, and a coating on said substrate,

said coating comprising pyrithione and a zinc compound selected from the group consisting of zinc salts of organic acids (e.g., zinc acetate), zinc salts of inorganic acids (e.g., zinc sulfate and 5 zinc chloride), zinc hydroxide, zinc oxide, and combinations thereof. Advantageously, the zinc compound is present in said coating in an amount of between 10 ppm and 90 ppm, more advantageously between 10 ppm and 70 ppm, based upon the weight of 10 the coating.

These and other aspects will become apparent upon reading the following detailed description of the invention.

It has now been surprisingly found in 15 accordance with the present invention that the addition of zinc to a composition containing pyrithione and ferric or cupric ion reduces or avoids a discoloration problem otherwise attributable to such composition. Without wishing 20 to be bound by any particular theory, the discoloration problem is believed to be caused by the formation of an insoluble iron pyrithione precipitate that not only discolors the composition, but also depletes the available pyrithione in sodium 25 pyrithione-containing compositions, thereby diminishing the antimicrobial efficacy of the composition.

The term "discoloration" as employed herein with respect to pyrithione-containing compositions 30 that also contain ferric ion or cupric ion dissolved therein is intended to describe any unacceptable gray, blue, black, purple, green, or color other than the natural color or desired artificial color

of the paint or paint base formulation. Starting materials employed in preparing the aqueous compositions of the present invention typically include tap water, as well as a source of pyrithione 5 in the form of sodium pyrithione, zinc pyrithione, and combinations thereof. It is noted, for example, that the natural color of sodium pyrithione itself is a clear yellow. It is quite common, however, for iron and/or copper contaminants to be introduced 10 into the aqueous composition from the tap water used, causing discoloration of the composition. One way of quantifying the discoloration is by measuring the reflectance color parameters, and calculating a whiteness value from them. Another method is to 15 visually inspect the composition for any signs of off-whiteness, as compared to the desired or white color.

In water-based paints, adhesives, caulk and sealants a level of ferric or copper ion of 10 ppm 20 or higher is not uncommon. By incorporating an effective amount of the zinc salt of an organic acid or inorganic acid, zinc hydroxide or zinc oxide or a mixture thereof into the composition, the blue 25 discoloration typically attributable to the presence of ferric ion bound with pyrithione is suitably reduced, eliminated or avoided, as is the green discoloration attributable to the presence of copper ion.

Although the amount of the above described zinc 30 salt of an organic acid or inorganic acid, zinc hydroxide or zinc oxide, or combination thereof, needed to prevent discoloration in the aqueous composition in which it is employed can vary over a

-8-

wide range of between 0.001% or lower to 10% or greater, based upon the weight of the aqueous composition in which it is employed, it has been surprisingly found in accordance with the present invention that the discoloration associated with tap water contamination by iron or copper is suitably reduced or avoided by incorporating into said composition an amount of between 10 ppm and 90 ppm, more advantageously between 10 ppm and 70 ppm, of the zinc ion. Although not wishing to be bound by any particular theory, the present inventors believe that the efficacy of such low levels of zinc ion in resolving the discoloration problem is attributable to a "common ion effect" forcing an equilibrium toward unionized zinc pyrithione where zinc ion, pyrithione ion, and unionized zinc pyrithione are all present in the composition.

The pyrithione used in the process and composition of this invention is preferably a pyrithione salt, such as sodium pyrithione, zinc pyrithione, chitosan pyrithione, magnesium disulfide pyrithione, and the like, although pyrithione acid can be used if desired. More preferable pyrithione salts include sodium pyrithione, and zinc pyrithione, most preferably zinc pyrithione.

The sodium pyrithione useful in the present invention is a well-known commercial product that is commonly made by reacting 2-chloropyridine-N-oxide with NaSH and NaOH, as illustrated by the disclosures of U.S. Pat. No. 3,159,640.

Zinc pyrithione may be made by reacting 1-hydroxy-2-pyridinethione (i.e., pyrithione acid) or a soluble salt thereof with a zinc salt (e.g.,

ZnSO_4) to form a zinc pyrithione precipitate, as illustrated by the disclosures of U.S. Pat. No. 2,809,971.

The aqueous compositions of the present invention are suitable for a variety of uses, such as, for example as soap, shampoo, skin care medicaments, paint, or incorporated into or onto plastic or a woven or non-woven fibers, when formulated to contain the requisite components in addition to the antimicrobial component.

The antimicrobial compositions of the present invention are particularly useful in the form of paints, including indoor and outdoor household paints, industrial and commercial paints. Particularly advantageous results are obtained when the compositions of the present invention are utilized as marine paints for use, for example, on ship's hulls. In addition, the antimicrobial compositions provide desirable results when the antimicrobial component is incorporated into exterior paints of the latex and alkyd types. The antimicrobial component of the aqueous composition is also useful as an "in-can" preservative during storage and prior to use of the paint.

Typically a paint composition will contain, in addition to the antimicrobial component, a resin, a pigment, and various optional additives such as thickening agent(s), wetting agents and the like, as is well known in the art. The resin is preferably selected from the group consisting of vinyl, alkyd, epoxy, acrylic, polyurethane and polyester resins, and combinations of thereof. The resin is preferably employed in an amount of between about

-10-

20% and about 80% based upon the weight of the paint or paint base.

In addition, the paint composition of the present invention optionally additionally contains optional additives which have a favorable influence on the viscosity, the wetting power and the dispersibility, as well as on the stability to freezing and electrolytes and on the foaming properties. If a marine paint is being fabricated, the paint preferably contains a swelling agent to cause the paint to gradually "slough off" in its marine environment, thereby causing renewed biocidal efficacy of newly exposed biocide at the surface of the paint in contact with the water medium of the marine environment. Illustrative swelling agents are naturally occurring or synthetic clays, such as kaolin, montomorillonite, and bentonite), clay mica (muscovite), and chlorite (hectonite), and the like. In addition to clays other swelling agents, including natural or synthetic polymers, such as that commercially available as POLYMERGEL, have been found to be useful in the compositions of the present invention to provide the desired "sloughing off" effect. Swelling agents can be used singly or in combination. The total amount of optional additives is preferably no greater than 20% by weight, more preferably between about 1% and about 5% by weight, based upon the total weight of the paint composition.

Illustrative, thickening agents include cellulose 30 derivatives, for example methyl, hydroxyethyl, hydroxypropyl and carboxymethyl cellulose, poly(vinyl alcohol), poly

(vinylpyrrolidone), poly(ethyleneglycol), salts of poly(acrylic acid) and salts of acrylic acid/acrylamide copolymers.

Suitable wetting and dispersing agents include
5 sodium polyphosphate, salts of low molecular weight poly(acrylic acid), salts of poly(ethane sulfonic acid), salts of poly(vinyl phosphonic acid), salts of poly(maleic acid) and salts of copolymers of maleic acid with ethylene, 1 olefins 3 to 18 carbon
10 atoms and/or styrene.

In order to increase the stability to freezing and electrolytes there may be added to the paint composition various monomer 1.2-diols for example glycol, propylene glycol (1.2) and butylene glycol 1.2) or polymers thereof, or ethoxylated compounds.
15 For example reaction products of ethylene oxide with long-chain alkanols, amines, alkyd phenols, poly(propyleneglycol), or poly(butylene glycol), or a combination thereof, or the like.

20 The minimum temperature of film formation (white point) of the paint composition may be reduced by adding solvents, such as ethylene glycol, butyl glycol, ethyl glycol acetate, ethyl diglycol acetate, butyl diglycol acetate, benzene or
25 alkylated aromatic hydrocarbons. As defoaming agents there are suitable for example poly(propylene glycol) and polysiloxanes. Optionally other biocides can additionally be incorporated into the paint formulations of the present invention. Useful optional solvents include methylisobutylketone
30 (herein referred to as "MIBK"), xylene, ethyl benzene, methanol, and combinations thereof.

The paint composition of the present invention may be used as a paint for natural or synthetic materials, for example wood, paper, metals, textiles and plastics. It is particularly suitable as an 5 outdoor paint, and is excellent for use as a marine paint.

Another significant use for the aqueous composition of the present invention is as a latex tile adhesive typically containing, for example, in 10 addition to the antimicrobial component, a latex emulsion, an optional rosin emulsion, an optional plasticizer, an optional antioxidant, and an optional pigment or filler (such as calcium carbonate). Yet another significant use for the 15 aqueous composition of the present invention is as a latex caulk, typically containing, in addition to the antimicrobial component, an acrylic latex, a nonionic surfactant, a dispersant, an optional plasticizer, and an optional pigment or filler (such 20 as calcium carbonate).

The aqueous antimicrobial compositions of the present invention are useful, in any of the variety of applications described herein, as disinfectants and preservatives, in a liquid or spreadable solid form, alone or in combination with an inert carrier such as water, liquid hydrocarbons, ethanol, 25 isopropanol, or the like. They can be employed using conventional procedures to control bacteria and fungi in various substrates, and can be applied 30 to bacterial or fungal organisms or their substrates in an antimicrobial amount by conventional procedures such as spraying, dipping, drenching impregnation, and the like.

-13-

The invention is further illustrated by the following Examples. Unless otherwise stated, the "parts" and "%" are "parts by weight" and "percent by weight", respectively.

5 While the invention has been described above with references to specific embodiments thereof, it is apparent that many changes, modifications and variations can be made without departing from the inventive concept disclosed herein. Accordingly, it
10 is intended to embrace all such changes, modifications and variations that fall within the spirit and broad scope of the appended claims.

15 The following examples are intended to illustrate, but in no way limit the scope of, the present invention.

-14-

EXAMPLE 1

Elimination of Blue Discoloration Caused by the
Presence of Pyrithione and Ferric Ion In a
Paint Base

5 Efficacy of zinc oxide in eliminating blue
coloration caused by the presence of ferric ion in
sodium pyrithione containing paint bases.

10 In order to test the effectiveness of zinc
oxide in eliminating or reducing blue color caused
by ferric ion in a pyrithione-containing paint, the
following experiment was conducted.

15 Two samples weighing 150 grams each of below
aqueous (latex) paint formulation containing sodium
pyrithione and zinc oxide were placed in plastic
cups. A wooden tongue depressor was then dipped
into each sample and then allowed to dry to provide
a control or "blank" comparison. Ferric chloride
was then added to each sample to provide a
concentration of 64 ppm of ferric ion in each
20 sample. Tongue depressor coatings were taken to
provide a basis for comparison. No discoloration
formed in the paints themselves or the dry films of
the painted tongue depressor.

-15-

Latex Paint Formulation Containing Sodium Pyritione and Zinc Oxide:		
	Ingredient	Grams
5	water	240.00
	hydroxyethyl cellulose	6.0
	Tamol 850 ^{1/}	14.2
	Ethylene Glycol	50.0
	Colloid 643 ^{2/}	2.0
	Triton® CF-10 ^{3/}	5.0
10	sodium pyritione 40% active	3.0
	potassium tripolyphosphate	3.0
	Pigment grind:	
15	titanium dioxide (Rutile)	424.0
	aluminum magnesium silicate	228.0
	attapulgite clay	3.0
	zinc oxide	50.0
	aluminum silicate	100.0
	propylene glycol	68.0
20	Let Down:	
	water	84.0
	acrylic latex emulsion 58.0% solids	700.0
	Colloid 643	6.0
	Texanol ^{4/}	18.6
25	hydroxyethyl cellulose 2.5% in water	236.4
	Total Mass in Grams	2243.2

¹An anionic dispersant, a product of Rohm and Haas Company.²A defoamer, a product of Rhone-Poulence Corp.³A nonionic surfactant, a product of Union Carbide Corp.⁴A coalescent, a product of Eastman Kodak Company

-16-

Next, as a comparison, two samples weighing 150 grams each of below aqueous (latex) paint formulation containing sodium Pyrithione and no zinc oxide were placed in paper cups. A wooden tongue 5 depressor was then dipped into each sample and then allowed to dry to provide a control or "blank" comparison. Ferric chloride was then added to each sample to provide a concentration of 64 ppm of ferric ion in each sample. The comparison coatings 10 on the tongue depressor were visually observed to provide a basis for the comparison. After 30 minutes a bluish gray discoloration formed in the paints themselves and the dry films of the painted tongue depressor.

-17-

Latex Paint Formulation Containing Sodium Pyrithione and Zinc Oxide:		
	Ingredient	Grams
5	water	240.0
	hydroxyethyl cellulose	6.0
	Tamol 850 ^{5/}	14.2
	Ethylene Glycol	50.0
	Colloid 643 ^{6/}	2.0
	Triton® CF-10 ^{7/}	5.0
10	sodium pyrithione 40% active	3.0
	potassium tripolyphosphate	3.0
	Pigment grind:	
	titanium dioxide (Rutile)	424.0
	aluminum magnesium silicate	228.0
15	attapulgite clay	3.0
	aluminum silicate	100.0
	propylene glycol	68.0
	Let Down:	
	water	84.0
20	acrylic latex emulsion 58.0% solids	700.0
	Colloid 643	6.0
	Texanol ^{8/}	18.6
	hydroxyethyl cellulose 2.5% in water	236.4
	Total Mass in Grams	2193.2

⁵An anionic dispersant, a product of Rohm and Haas Company⁶A defoamer, a product of Rhone-Poulence Corp.⁷A nonionic surfactant, a product of Union Carbide Corp.⁸A coalescent, a product of Eastman Kodak Company

-18-

EXAMPLE 2

Elimination of Blue Discoloration Caused by the
Presence of Pyrithione and Ferric Ion In a Paint

Efficiency of zinc oxide in eliminating blue
5 coloration caused by the presence of ferric ion in
zinc pyrithione containing paint.

In the presence of ferric ion, zinc pyrithione-containing paint compositions also tended to turn blue to gray, although at a much slower rate than
10 did the sodium pyrithione-containing paints.

48 percent aqueous zinc pyrithione was added to a white paint which contained 1.0 percent zinc oxide to provide a level of 3000 ppm of zinc pyrithione in the sample. Ferric chloride was then added to
15 provide a concentration of 64 ppm of ferric ion in the sample. Upon standing for a month, the paint was found to have no discoloration.

When this composition is painted over bare steel or copper, no discoloration is detected. This
20 result is surprising, since the copper would have been expected to turn the paint a greenish color, and the steel would have been expected to turn the paint a bluish color.

As a comparison, 48 percent aqueous zinc
25 pyrithione is added to a white paint containing no zinc oxide to provide a level of 3000 ppm of zinc pyrithione in the sample. Ferric chloride is then added to provide a concentration of 64 ppm of ferric ion in the sample. Upon standing for a week, the
30 paint is found to turn bluish in color.

-19-

EXAMPLE 3

Process for the Removal of Discoloration Caused
by the Presence of Pyrithione and Ferric Ion
in Water-based Coatings

5 48 percent aqueous zinc pyrithione was added to
a white paint sample to provide a level of 3000 ppm
of zinc pyrithione in the sample. Ferric chloride
was then added to provide a concentration of 25 ppm
of ferric ion in the sample. Upon standing for two
10 days, the paint was found to turn bluish in color.
To this point 0.007 percent (70 ppm) of zinc sulfate
was added and the paint was mixed for 5 minutes.
After sitting for an additional 5 minutes it was
observed that the paint had whitened and the bluish
15 color was no longer noticeable. The addition of the
zinc sulfate to this paint had removed the blue
color which was formed from the addition of zinc
pyrithione and ferric chloride.

-20-

WHAT IS CLAIMED IS:

1. A process for inhibiting the formation of discoloration in an aqueous composition selected from the group consisting of water-based paint,
5 adhesive, caulk and sealant compositions, and combinations thereof, wherein said discoloration is caused by the presence of ferric ion or cupric ion together with pyrithione in said composition, characterized by contacting the composition with a
10 discoloration-inhibiting amount of a zinc compound selected from the group consisting of zinc salts of organic acids, zinc salts of inorganic acids, zinc hydroxide, zinc oxide, and combinations thereof.
2. The process of claim 1 characterized in
15 that said discoloration-inhibiting amount of said zinc compound in said composition is between 10 ppm and 90 ppm.
3. The process of claim 1 characterized in
20 that said discoloration-inhibiting amount of said zinc compound is between 10 ppm and 70 ppm.
4. The process of claim 1 characterized in that said zinc compound is selected from the group consisting of zinc acetate, zinc sulfate, zinc chloride, and combinations thereof.

5. A process for removing an undesirable discoloration in an aqueous antimicrobial composition containing a dissolved metal ion selected from the group consisting of ferric ion, cupric ion, and combinations thereof, and containing pyrithione, characterized by contacting said composition with a zinc ion in a molar amount at least equal to the amount of said dissolved metal ion in said composition.
- 10 6. The process of claim 5 characterized in that said amount of said zinc compound in said composition is between 10 ppm and 90 ppm.
- 15 7. The process of claim 5 characterized in that said amount of said zinc compound is between 10 ppm and 70 ppm.
- 20 8. The process of claim 5 characterized in that said zinc ion is contacted with said composition using a zinc compound selected from the group consisting of zinc salts of organic acids, zinc salts of inorganic acids, zinc hydroxide, zinc oxide, and combinations thereof.

-22-

9. An aqueous antimicrobial composition,
protected against discoloration attributable to the
presence of ferric ion or cupric ion therein, said
composition being selected from the group consisting
5 of water-based paints, adhesives, caulk and
sealants, and combinations thereof, said composition
being characterized by comprising water, an organic
base medium and zinc ion, said zinc ion being
present in said composition in an amount of between
10 10 ppm and 90 ppm.

10. A coated substrate comprising a substrate
selected from the group consisting of ferrous metal-
containing substrates, copper-containing substrates,
and combinations, and a coating on said substrate,
15 said coating being characterized by comprising
pyrithione and a zinc compound selected from the
group consisting of zinc salts of organic acids,
zinc salts of inorganic acids, zinc hydroxide, zinc
oxide, and combinations thereof.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/09722

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :C09K 15/28, 15/32; B32B 15/04

US CL :428/469, 472; 106/15.05, 18.32, 18.33, 18.36; 252/400.52, 472

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 428/469, 472; 106/15.05, 18.32, 18.33, 18.36; 252/400.52, 472

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS; pyrithione, zinc, discoloration

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 4,161,526 (GORMAN) 17 July 1979, column 1, lines 44-54.	1-10
A	US, A, 4,818,436 (FRENCH ET AL.) 04 April 1989.	1-10
A	US, A, 4,396,766 (FARMER, JR. ET AL.) 02 August 1983.	1-10
A	US, A, 4,482,715 (TROTZ ET AL.) 13 November 1984.	1-10
A	US, A, 4,888,368 (KOHL ET AL.) 19 December 1989.	1-10
A	US, A, 4,957,658 (FRENCH ET AL.) 18 September 1990.	1-10
Y	US, A, 5,227,156 (WIESE) 13 July 1993, column 3, lines 32-45.	1-10

 Further documents are listed in the continuation of Box C.

See patent family annex.

- * Special categories of cited documents:
- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed
- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "Z" document member of the same patent family

Date of the actual completion of the international search

14 NOVEMBER 1995


Date of mailing of the international search report

06 DEC 1995

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Authorized officer

TIMOTHY M. SPEER



Facsimile No. (703) 305-3230

Telephone No. (703) 308-2351

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/09722

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 5,137,569 (WALDRON ET AL.) 11 August 1992, column 2, lines 27-33.	1-10